



4-346DST DST Hinge Pr01 160°



Avantages

- For nested doors.
- Hinge visible.
- RH and LH version.
- 160° Opening angle.
- With DIRAK-SNAP-Technology.
- Lift-off.
- The installation of the frame-part and door-part is tool-less, achieved by a simple push into the appropriate cutouts.

Materials

- **Hinge-parts:** zinc die, matte black
- **Solid pin, pressed in:** stainless steel
- **Spacer:** Teflon, black
- **Snap wedges:** sintered steel

Notes

1. spacer



Hinge

Part Number	Clamping range (S)	Version	Pin version	Installation type	Delivery Unit
417-9007.00-00010	0.7 - 1.2 mm	RH version	pressed in	tool-less	10 pcs.
417-9007.00-00015	1.2 - 1.7 mm	RH version	pressed in	tool-less	10 pcs.
417-9007.00-00020	1.7 - 2.2 mm	RH version	pressed in	tool-less	10 pcs.
417-9007.00-00030	2.7 - 3.2 mm	RH version	pressed in	tool-less	10 pcs.
417-9008.00-00010	0.7 - 1.2 mm	LH version	pressed in	tool-less	10 pcs.
417-9008.00-00015	1.2 - 1.7 mm	LH version	pressed in	tool-less	10 pcs.
417-9008.00-00020	1.7 - 2.2 mm	LH version	pressed in	tool-less	10 pcs.
417-9008.00-00030	2.7 - 3.2 mm	LH version	pressed in	tool-less	10 pcs.

292-0306.80-02530 **Tool for uninstallation**

292-0401.00-03010 **Cutout-cover**

292-0702.15-01030 **Reinforcement plate for cutout**

